















Nightspot B/RGBW Gobo pole luminaire

Monochrome: With 1 x high performance LED module, CRI: > 70, Colour tolerance: max. 4 SDCM
Service life: L70/B20 > 50 000 h
protection class I or II, IP67 , IK08
integral driver (AC/DC)

RGBW: With 1 x RGBW high performance LED module, protection class I, IP67 , IK08
external DMX-controller required, connection with hybrid cable 230 V/DMX, RDM compatible integral driver (AC/DC)

windage area AW 0.085 m²,
corrosion-resistant die cast aluminium housing AlSi12 and aluminium profile, polyester powder coated, focusable lens, carrier for gobos and colour filters, all exterior steel parts are stainless steel, tempered safety glass, silicon gasket, closure with 4 stainless steel screws, for pole diameter Ø 60–100 mm, rotatable, powder coated aluminium mounting base: 2 drilled holes Ø 9 mm, spacing 105 mm, 1 centre hole Ø 22 mm, tilt range 80°, swivel range 180°, M20 cable gland



Nightspot B Gobo pole luminaire, 63 mm focal length

Part number*	Colour	Light source	Luminous flux	Beam angle
8 987 244 059	black	1 x LED module 47 W	1000 lm	30°
8 987 264 059	white	cool white (6500 K)		
8 987 254 059	silver grey			

Nightspot B Gobo pole luminaire, 85 mm focal length

Part number*	Colour	Light source	Luminous flux	Beam angle
8 987 244 049	black	1 x LED module 47 W	1095 lm	20°
8 987 264 049	white	cool white (6500 K)		
8 987 254 049	silver grey			

Nightspot B Gobo pole luminaire, 150 mm focal length

Part number*	Colour	Light source	Luminous flux	Beam angle
8 987 244 019	black	1 x LED module 47 W	907 lm	12°
8 987 264 019	white	cool white (6500 K)		
8 987 254 019	silver grey			

Part number*	Protection class I luminaire
1 ..	Dimmable version (DALI)
2 ..	Dimmable version (1-10 V)
	Protection class II luminaire
5 ..	Luminaire not dimmable
6 ..	Dimmable version (DALI)
7 ..	Dimmable version (1-10 V)

*Luminaires available in 2700 K or 3000 K on request

Nightspot B RGBW Gobo pole luminaire, 63 mm focal length

Part number	Colour	Light source	Luminous flux	Beam angle
8 987 249 059	black	1 x LED module RGBW	max. 525 lm	30°
8 987 269 059	white	W = 6000 K		
8 987 259 059	silver grey	(max. 38 W)		

Nightspot B RGBW Gobo pole luminaire, 85 mm focal length

Part number	Colour	Light source	Luminous flux	Beam angle
8 987 249 049	black	1 x LED module RGBW	max. 575 lm	20°
8 987 269 049	white	W = 6000 K		
8 987 259 049	silver grey	(max. 38 W)		

Nightspot B RGBW Gobo pole luminaire, 150 mm focal length

Part number	Colour	Light source	Luminous flux	Beam angle
8 987 249 019	black	1 x LED module RGBW	max. 476 lm	12°
8 987 269 019	white	W = 6000 K		
8 987 259 019	silver grey	(max. 38 W)		

LED (see page 185)

