Data Sheet E2 LED Edgelight DALI Emergency



CAT NO. 684730/D, 684731/D, 684733/D





684731/D

684730/D

Cat No	684730/D	684731/D	684733/D
Supply Voltage	240V a.c. (+/- 6%) 50 Hz		
Operating Mode	Maintained		
Energy consumption	2.6W hrc/ 1.8W lrc		
Battery pack	3 x AF NiMH stick 2.1Ah 3.6V		
Operating Temperature	10°C to 40°C		
IP Rating	IP21		
Body Construction	Injection moulded polycarbonate		
Diffuser	Injection moulded acrylic		
Compliance	IEC 62385 AS/NZS	5 2293 AS/NZS 60590 🙆	


*hrc- high rate charge, lrc- low rate charge

E2 LED Edgelight DALI Emergency


CAT NO. 684730/D, 684731/D, 684733/D



Dimensions:







Recessed Cut out: Refer installation instructions

- Premium Exit sign for a wide range of Emergency Lighting applications
- DALI monitored
- All-in-one recessed and surface mounting versions for single and double-sided installation
- Long life LED light source using latest LED strip technology
- 3W maximum consumption (2.2W typical illuminated on Low rate charge)
- Dual rate + pulsed charging for maximum life of high temperature NiMH batteries
- Running Man decal options included
- Manufactured in Australia

Recessed or Surface-mounted			
684730/D	E2 Recessed/Surface Maint + 4 Running Man decals		
Classification			
	C0 C8 C90 C16		
Surface-moun	ted		
684731/D	E2 Surface only, Maint + 4 Running Man decals		
684733/D	E2 Surface only, Maint + 3 R Man decal – BLACK		
Accessories			
684735	E2 Lens Replacement Kit		
684736	E2 Recess Plate Kit White		
684737	E2 Mounting Block Kit White		
684738	E2 Recess Plate Kit Black		
684739	E2 Surface Mounting Block Kit Black		

Legrand - Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Legrand - New Zealand 0800 476 009 www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.