

# Data Sheet



## G2 LED Slide Connect Exit Sign



CAT NO. 686200, 686201, 686203, 686204, 686206, 686207, 686208,  
686209, 686211, 686212



686200

Specifications		
Mode of operation	Maintained	
Supply voltage	240V a.c. +/- 6% 50Hz	
Power consumption	4.6W	5.3W
Battery	NICd 2x2 Sub-C cells linear - 4.8Vdc 1.5Ah	
Operating temperature	10° to 40°	
IP Rating	IP20	
Lamp	1x1W HBLED	
Body construction	ABS	
Compliance	AS/NZS 2293 AS/NZS60598  	

# G2 LED Slide Connect Exit Sign

CAT NO. **686200, 686201, 686203, 686204, 686206, 686207, 686208, 686209, 686211, 686212**



686200

- Low energy consumption and heat dissipation - save up to 70% on energy consumption\*
- Unique single LED maintained exit sign (patent pending)
- Long life LED light source - up to 50,000 hours
- Retrofits to previous generation Minitronics Slide Connect bracket
- High resistance polycarbonate clear cover and white ABS housing
- One box solution
- Can be wall, ceiling or cantilever mounted
- High temperature NiCd batteries
- Large terminal block for ease of connection
- Stand alone and Axiom versions available
- Low cost maintenance
- Available in White, Silver and black body
- Manufactured in Australia

\*When compared with traditional fluorescent lighting

SPU	
Cat No.	Description
686200	White body c/w running man sheets (set of 4)
686201	White body c/w EXIT sheets, Peel-off-arrow (set of 3)
686208	Silver body c/w Running man sheets (set of 4)
686209	Silver body c/w EXIT sheets, Peel-off-arrow (set of 3)
686206	Black body less diffuser sheets (no downward lens)

Computer Monitored SPU's AXIOM Wireless	
Cat No.	Description
686203	White body c/w running man sheets (set of 4)
686204	White body c/w EXIT sheets, Peel-off-arrow (set of 3)
686211	Silver body c/w running man sheets (set of 4)
686212	Silver body c/w EXIT sheets, Peel-off-arrow (set of 3)
686207	Black body less diffuser sheets (no downward lens)

Accessories	
Cat No.	Description
686214	Battery pack replacement for LSC
686215	Cantilever bracket, White
686216	Wire suspension kit, silver pair of 2
686220	Runningman straight green on black
686232	Runningman left green on black
686233	Runningman right green on black
686235	Wire guard single sided
686236	Wire guard double sided

Classification				
	C <sub>0</sub>	C <sub>90</sub>	C <sub>0</sub>	C <sub>90</sub>
686200	D1.25	A1.25	E1.6	E1.6
686201	D1.25	A1.25	E1.6	E1.6
686203	D1.25	A1.25	E1.6	E1.6
686204	D1.25	A1.25	E1.6	E1.6
686208	D1.25	A1.25	E1.6	E1.6
686209	D1.25	A1.25	E1.6	E1.6
686211	D1.25	A1.25	E1.6	E1.6
686212	D1.25	A1.25	E1.6	E1.6

Classification	Maximum spacing between luminaires						
	Mounting Height (Metres)						
Metres	2.1	2.4	2.7	3	3.3	3.6	4
A1.25	2.5	2.4	2.2	1.9	1.3		
A1.6	2.8	2.8	2.7	2.5	2.2	1.8	
D1.25	4.0	3.8	3.4	2.9	2.0		
E1.6	4.8	4.8	4.8	4.4	4.0	4.2	3.8

Legrand - Australia  
1300 369 777  
www.legrand.com.au  
ABN 31 000 102 661

Legrand - New Zealand  
0800 476 009  
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.