



Features

This IP65 Polycarbonate LED weatherproof fitting, brings a new level of value. Featuring security clips that can be screwed closed, or stainless steel clips for longevity this product will meet your demands.

Perfect for loading docks, chillers or under eaves this product will give you significant energy and maintenance savings.

Operating Temperature -20 degrees to +50 degrees

Colour Temperature 4000K

Benefits:

- Clips to support the gear tray during installation
- Quick connect gear tray
- Anti vandal clips
- Low glare diffuser

Applications

Commercial

Lifetime

2 Year Guarantee

L70 30,000 Hours



For technical details, see page 2

RX Nix LED

WATTS	58w, 48w, 30w, 23w & 12w
LUMEN OUTPUT	993lm - 5,034lm
CCT & RX	4000k
CRI	80
BEAM ANGLE	N/A
IP RATING	IP65
IK RATING	IK08
IES FILES AVAILABLE?	Yes
UGR	N/A
DIMMING / CONTROLS / DRIVER	N/A
LIFETIME	30,000hrs L70 B50
WARRANTY	2 years
DIMENSIONS L,W,H	655mm x 89mm x 92 mm 1265mm x 89mm x 92 mm 1565mm x 89mm x 92 mm 655mm x 130mm x 92 mm 1265mm x 130mm x 92 mm 1565mm x 130mm x 92 mm
MATERIALS	Polycarbonate
BODY COLOUR	Grey
MOUNTING OPTIONS	Surface
CONNECTION EG FLEX & PLUG / TERMINAL	Terminal

ORDER CODE	DESCRIPTION
REXNIX25LED	RX NIX UNDERVERANDAH LED 25 IP65 58W
REXNIX24LED	RX NIX UNDERVERANDAH LED 24 IP65 48W
REXNIX15LED	RX NIX UNDERVERANDAH LED 15 IP65 30W
REXNIX14LED	RX NIX UNDERVERANDAH LED 14 IP65 23W
REXNIX22LED	RX NIX UNDERVERANDAH LED 22 IP65 23W
REXNIX12LED	RX NIX UNDERVERANDAH LED 12 IP65 11.5W
REXNIXLEDSSCLIP	RX NIX STAINLESS STEEL CLIPS