



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

NOVIEL L ASYM

Description Product map

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Asymmetric polished / matt reflector (ASP / ASM) Asymmetric polished reflector + transparent cover (APT) Asymmetric matt reflector + transparent cover (AMT)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA)
MATERIALS	Cover: transparent PMMA Diffuser: microprismatic PMMA Housing: sheet steel Reflector: polished / matt anodized aluminium Trim: sheet steel
SURFACE FINISH	Trim: white RAL 9003 (W03)
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C

AREAS OF APPLICATION ARCHITECTURE AND MEDIA
 RETAIL AND PRESENTATION



Accessories

List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
NOVIEL L ASYM POLISHED REF IP40 LED 2550lm/830 1x29W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 2700lm/840 1x29W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 2850lm/830 1x33W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 3050lm/840 1x33W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2450lm/830 1x29W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2550lm/840 1x29W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2750lm/830 1x33W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2900lm/840 1x33W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 2550lm/830 1x29W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 2850lm/830 1x33W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 3050lm/840 1x33W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 2700lm/840 1x29W, FIX, RAL 9003		RFA / 3DS / IES / LDT /

	CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2450lm/830 1x29W, FIX, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2550lm/840 1x29W, FIX, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2750lm/830 1x33W, FIX, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2900lm/840 1x33W, FIX, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 2550lm/830 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 2700lm/840 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 2850lm/830 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED REF IP40 LED 3050lm/840 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 2550lm/830 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 2850lm/830 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 3050lm/840 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT REF IP40 LED 2700lm/840 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2450lm/830 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT /

NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2550lm/840 1x29W, DALI, RAL 9003	CURVE / RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2750lm/830 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM POLISHED+TRANSPARENT IP44 LED 2900lm/840 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2450lm/830 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2550lm/840 1x29W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2750lm/830 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /
NOVIEL L ASYM MATT+TRANSPARENT IP44 LED 2900lm/840 1x33W, DALI, RAL 9003	RFA / 3DS / IES / LDT / CURVE /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.