



PRODUCT DETAILS



Dimensions



PLAST 2 LED

PLAST 2 LED OPAL LED 1450lm/840
1x14W, FIX, -

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Opal diffuser (OPD)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: PMMA Housing: white PC
SURFACE FINISH	Housing: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	1450 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	14 W
SYSTEM EFFICACY	104 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP65
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS (L x W x H)	300 x 300 x 90 mm
WEIGHT	2 kg

AREAS OF APPLICATION HOSPITALITY

HOUSE AND FLAT


HEALTH AND CARE



Accessories



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.