



## Features & Benefits

Backlit panel can be covered as it offers excellent thermal management with an IC-4 rating. The range includes a 4000K panel as well as a tri-colour option in all sizes. The panel also offers low glare UGR19.

Available in 600x600mm, 300x1200mm & 600x1200mm

## Applications

Offices  
Schools  
Retail  
Commercial

## Lifetime

50,000 hours  
5 year warranty




For technical details, see page 2

## RX Backlit LED Panel

<b>CODE</b>	REXBLP66	REXBLP123	REXBLP126
<b>WATTS</b>	36W	36W	60W
<b>COLOUR TEMPERATURE</b>	4000K		
<b>LUMEN OUTPUT</b>	3453lm	3200lm	6277lm
<b>EFFICACY</b>	96lm/W	89lm/W	105lm/W
<b>CRI</b>	CRI>80		
<b>SDCM</b>	<3		
<b>BEAM ANGLE</b>	90°		
<b>IP RATING</b>	IP44		
<b>IK RATING</b>	-		
<b>IC RATING</b>	IC-4		
<b>IES FILES AVAILABLE?</b>	Yes		
<b>UGR</b>	UGR19		
<b>DIMMING / CONTROLS / DRIVER</b>	Non-dimmable		
<b>LIFETIME</b>	L80 50,000hrs B10		
<b>WARRANTY</b>	5 years		
<b>DIMENSIONS</b>	595x595x30mm	295x1195x30mm	595x1195x30mm
<b>POWER FACTOR</b>	0.9		
<b>VOLTAGE &amp; FREQUENCY</b>	230V 50Hz		
<b>WORKING TEMP</b>	-20°C to +40°C		
<b>WEIGHT</b>	1.89kg	2.04kg	3.75kg
<b>MATERIALS</b>	Aluminum with PS diffuser		
<b>FRAME COLOUR</b>	White		
<b>MOUNTING OPTIONS</b>	Recessed		
<b>STANDARDS &amp; RATINGS EG CA</b>	AS/NZS 60598 Part 2.2		
<b>CONNECTION EG FLEX &amp; PLUG / TERMINAL</b>	Flex & Plug		

## Photometric Diagrams

ORDER CODE	DESCRIPTION
REXBLP66	BACKLIT PANEL LED 600X600MM 36W 4K
REXBLP123	BACKLIT PANEL LED 1200X300MM 36W 4K
REXBLP126	BACKLIT PANEL LED 1200X600MM 60W 4K



## RX Backlit LED Panel Tri Colour

CODE	REXBLP66CCT			REXBLP123CCT			REXBLP126CCT		
WATTS	36W			36W			60W		
COLOUR TEMPERATURE	3000K	4000K	5700K	3000K	4000K	5700K	3000K	4000K	5700K
LUMEN OUTPUT	3056lm	3311lm	3093lm	3034lm	3303lm	3074lm	5891lm	6583lm	6277lm
EFFICACY	85lm/W	92lm/W	86lm/W	85lm/W	92lm/W	86lm/W	99lm/W	110lm/W	105lm/W
CRI	CRI>80								
SDCM	<3								
BEAM ANGLE	90°								
IP RATING	IP44								
IK RATING	-								
IC RATING	IC-4								
IES FILES AVAILABLE?	Yes								
UGR	UGR19								
DIMMING / CONTROLS / DRIVER	Non-dimmable								
LIFETIME	L80 50,000hrs B10								
WARRANTY	5 years								
DIMENSIONS	595x595x30mm			295x1195x30mm			595x1195x30mm		
POWER FACTOR	0.9								
VOLTAGE & FREQUENCY	230V 50Hz								
WORKING TEMP	-20°C to +40°C								
WEIGHT	1.89kg			2.04kg			3.75kg		
MATERIALS	Aluminium with PS diffuser								
FRAME COLOUR	White								
MOUNTING OPTIONS	Recessed								
STANDARDS & RATINGS EG CA	AS/NZS 60598 Part 2.2								
CONNECTION EG FLEX & PLUG / TERMINAL	Flex & Plug								

## Photometric Diagrams

ORDER CODE	DESCRIPTION
REXBLP66CCT	BACKLIT PANEL LED 600X600MM 36W TRI-COLOUR
REXBLP123CCT	BACKLIT PANEL LED 1200X300MM 36W TRI-COLOUR
REXBLP126CCT	BACKLIT PANEL LED 1200X600MM 60W TRI-COLOUR

