



Features & Benefits

The new RX Lighting HiPro Highbay comes in 2 wattages, 150 and 200 and is designed to replace 400w HID lamps. Fitting is IP65 but is designed for undercover use. Comes complete with 1.5m of flex and standard 3 pin plug.

Beam angles options available 120°, 90°, and 50° to allow for various mounting heights

Optional accessories include 90 degree Ali reflector, polycarbonate reflector with diffuser, 90 and 50 degree lens kits, bracket, chain, and daylight/movement sensor with 15m range.

High performance Nichia SMD chips and Meanwell driver

Applications

Shop, Warehouse, Commercial, Industrial

Lifetime

50000hrs

5 yr warranty

230 V
50 Hz

LED



IP
65



For technical details, see page 2

RX HiPro Highbay

WATTS	150W	200W
LUMEN OUTPUT	22,500lm	30,000lm
EFFICACY	150lm/w	
CCT & RX	4000k	
CRI	Ra >70	
BEAM ANGLE	120°	
IP RATING	IP65	
IK RATING	IK10	
IES FILES AVAILABLE?	Yes	
UGR	32	
DIMMING / CONTROLS / DRIVER	1-10V	
LIFETIME	50,000hr	
WARRANTY	5 years	
DIMENSIONS	292mm x 178mm (without bracket)	292mm x 197mm (without bracket)
POWER FACTOR	≥0.9	
VOLTAGE & FREQUENCY	230V 50/60Hz	
WORKING TEMP	-30°C ~ +50°C	-30°C ~ +45 °C
WEIGHT	5.1kg	5.7kg
MATERIALS	Aluminum	
BODY COLOUR	Black	
MOUNTING OPTIONS	Suspended	
STANDARDS & RATINGS EG CA	CE, RoHS, SAA	
CONNECTION EG FLEX & PLUG / TERMINAL	1.5m flex and standard 3 pin plug	

ORDER CODE	DESCRIPTION	CARTON QTY
REXHB12150W	HIPRO HIGHBAY 150W 4K 22,500LM 120DEG 1-10V DIAMETER 292MM	1
REXHB12200W	HIPRO HIGHBAY 200W 4K 30,000LM 120DEG 1-10V DIAMETER 292MM	1
REXHBPCREFDIF	HIPRO HIGHBAY PC REFLECTOR WITH DIFFUSER	
REXSHB50LENS	HIPRO HIGHBAY 50 DEGREE LENS ACCESSORY	
REXSHB90LENS	HIPRO HIGHBAY 90 DEGREE LENS ACCESSORY	
REXHBREMOTE	HIPRO HIGHBAY REMOTE FOR REXHBSSENSOR2	
REXHBSSENSOR2	HIPRO HIGHBAY DAYLIGHT AND OCCUPANCY REMOTE CONTROL SENSOR	
REXHB90ALIREF	HIPRO HIGHBAY 90 DEGREE ALI REFLECTOR	
REXHBSCHAIN1.5M	HIPRO HIGHBAY SAFETY CHAIN 1.5M	
REXHB12ADJBKT45	HIPRO HIGHBAY ADJUSTABLE BRACKET 45DEGREE	