



## Features & Benefits

Uniform light on surfaces with a slim profile. IP54 suitable for use in bathrooms.

Dimmable and available in 3 wattages 12W, 18W and 30W.

Pre-selectable colour correlated temperature 3000K / 4000K / 5700K.

Easy fix bracket system that allows for quick installation. Double insulated, does not require an earth,

## Applications

Indoor use only

Residential

Commercial

## Lifetime

40,000hrs

3 yr warranty



For technical details, see page 2

## RX Square Selene Oyster

<b>WATTS</b>	12W	18W	30W
<b>LUMEN OUTPUT</b>	1300lm +/- 4%	1850lm +/- 4%	3000lm +/- 4%
<b>EFFICACY</b>	108lm/w	110lm/W	100lm/W
<b>COLOUR TEMPERATURE</b>	3000K / 4000K / 5700K (TRI-COLOUR)		
<b>CRI</b>	Ra > 80		
<b>BEAM ANGLE</b>	120°		
<b>IP RATING</b>	IP54		
<b>IK RATING</b>	-		
<b>IC RATING</b>	N/A		
<b>IES FILES AVAILABLE</b>	Yes		
<b>UGR</b>			
<b>DIMMING / CONTROLS / DRIVERS</b>	Triac Dimmable LED driver		
<b>LIFETIME</b>	40,000hrs		
<b>WARRANTY</b>	3 years		
<b>DIMENSIONS</b>	250×250×50mm	300×300×40mm	400×400×51mm
<b>POWER FACTOR</b>	0.9		
<b>VOLTAGE &amp; FREQUENCY</b>	230V 50Hz		
<b>WORKING TEMPERATURE</b>	-20°C ~+ 45°C		
<b>WEIGHT</b>	750g	960g	2kg
<b>MATERIALS</b>	Polycarbonate		
<b>BODY COLOUR</b>	White		
<b>MOUNTING OPTIONS</b>	Surface mount		
<b>APPLICABLE STANDARD/S</b>	AS/NZS 60598		
<b>CONNECTION E.G. FLEX &amp; PLUG / TERMINAL</b>	Terminal Block		

ORDER CODE	DESCRIPTION
REXSEL12CCTSQ	RX SELENE OYSTER CCT 12W SQ 250X250X50MM WHITE IP54
REXSEL18CCTSQ	RX SELENE OYSTER CCT 18W SQ 300X300X40MM WHITE IP54
REXSEL30CCTSQ	RX SELENE OYSTER CCT 30W SQ 400X400X51MM WHITE IP54