# Worktitude for light


#### UR1SQ0465AS940NG



# URBAN 100 SQ 400 IP65 NW ASYM GR

#### Description:

Recessed outdoor wall floodlight, model URBAN 100, LAMP brand. Made of injected aluminium and painted in textured grey, with tempered glass. Clamping box included. Model for LED HI-POWER with 4000K colour temperature, CRI 90, and control gear included. IP65, IK07 protection rating. Insulation class I. Lifetime: 50 000 L90 B10



Finish: Texturised grey

**Dimensions:** 105 x 105 x 63 mm **Weight:** 708 g

Installation: Wall recessed

Recessing measures: 95 x 95 x 0 mm

# **TECHNICAL SPECIFICATIONS:**

 Light output:
 113 lm
 °K:
 4000

 Plum:
 1,7W
 CRI:
 90

 Efficacy:
 66,5 lm/w
 MacAdam:
 3

Type: HIGH POWER Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 1W

#### Light output tolerance +/- 10%



















# **CUSTOM MADE OPTIONS:**








UR1SQ0465AS940NG


# URBAN 100 SQ 400 IP65 NW ASYM GR


#### **PHOTOMETRIC DATA:**


UR1SQ0465AS940NG  $\eta = 100\%$ Imax = 833 cd/klm UTE:

CIE: 23 56 90 100 100











# ACCESORIES:

**Assembly** 



Product code: Description:

CT4P67N ACC. IP67 4P CONNECTOR