

# PRODUCT DATASHEET

## LED SST GIMBLE DL 10 W 4000 K KIT

LED SUPERSTAR GIMBLE DOWNLIGHT | LED downlight luminaires



---

### AREAS OF APPLICATION

- Living areas (living rooms, dining rooms, bedrooms etc.)

---

### PRODUCT FEATURES

- Lifetime: up to 30,000 h
- Adjustable swivel angle:  $\pm 30^\circ$
- Beam angle:  $60^\circ$
- Available with color temperature: 3,000 K, 4,000 K



## TECHNICAL DATA

### Electrical data

Nominal wattage	10.00 W
Nominal voltage	220...240 V
Mains frequency	50 Hz

### Photometrical data

Color temperature	4000 K
Color rendering index Ra	80
Light color (designation)	Cool White
Luminous flux	920 lm
Luminous efficacy	92 lm/W

### Dimensions & weight

Width	105.0 mm
Height	71.5 mm
Product weight	280.00 g
Cable length	1200 mm

### Colors & materials

Body material	Polycarbonate (PC)
Housing color	White
Product color	White

### Temperatures & operating conditions

Ambient temperature range	-20...45 °C
---------------------------	-------------

### Lifespan

Lifespan	30000 h
----------	---------

### Additional product data

Mounting type	Recessed
Mounting location	Ceiling

### Capabilities

Dimmable	Yes
----------	-----

### Certificates & standards

Protection class	II
Type of protection	IP40

---

**EQUIPMENT / ACCESSORIES**

- Equipped with 1.2 m cable and plug

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075132412	Folding carton box 1	282 mm x 72 mm x 282 mm	362.00 g	5.73 dm <sup>3</sup>
4058075132429	Shipping carton box 24	383 mm x 303 mm x 311 mm	9379.00 g	36.09 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.