

PRODUCT DATASHEET

LED SST GIMBLE DL 7 W 4000 K KIT

LED SUPERSTAR GIMBLE DOWNLIGHT | LED downlight luminaires



AREAS OF APPLICATION

- Living areas (living rooms, dining rooms, bedrooms etc.)

PRODUCT FEATURES

- Lifetime: up to 30,000 h
- Adjustable swivel angle: $\pm 30^\circ$
- Beam angle: 60°
- Available with color temperature: 3,000 K, 4,000 K



TECHNICAL DATA

Electrical data

Nominal wattage	7.00 W
Nominal voltage	220...240 V
Mains frequency	50 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	80
Light color (designation)	Cool White
Luminous flux	630 lm
Luminous efficacy	90 lm/W

Dimensions & weight

Width	85.0 mm
Height	64.5 mm
Product weight	220.00 g
Cable length	1200 mm

Colors & materials

Body material	Polycarbonate (PC)
Housing color	White
Product color	White

Temperatures & operating conditions

Ambient temperature range	-20...45 °C
---------------------------	-------------

Lifespan

Lifespan	30000 h
----------	---------

Additional product data

Mounting type	Recessed
Mounting location	Ceiling

Capabilities

Dimmable	Yes
----------	-----

Certificates & standards

Protection class	II
Type of protection	IP40

EQUIPMENT / ACCESSORIES

- Equipped with 1.2 m cable and plug

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075132436	Folding carton box 1	110 mm x 110 mm x 80 mm	296.00 g	0.97 dm ³
4058075132443	Shipping carton box 30	350 mm x 240 mm x 425 mm	9546.00 g	35.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.