

X line is a range of LED luminaires. They are designed for mounting on walls for bathrooms, hospitals and can be fitted in continuous lines.

Features:

Aluminium profile and opal polycarbonate diffuser.
Electronic gear built in the luminaire.

Fitting:

Surface mounted. Can fitted as individual modules or in continuous lines.
Suspension elements not included.



Power

LED 11W, 16W, 18W, 32W, 27W, 47W, 36W, 62W

Beam

126°

Colour temperature

3000K warm white - CRI \geq 80

4000K neutral white - CRI \geq 80

Nominal lumen output

11W - 1300lm, 16W - 2200lm, 18W - 2600lm, 32W - 4400lm, 27W - 3900lm,
47W - 6600lm, 36W - 5200lm, 62W - 8800lm

Control gear

Electronic (EL)

IP

IP44 - IK04

Finishes

Grey

Supply voltage

220... 230V, 50/60Hz

Installation

Surface mounted


Features



LED



LED and control gear included



11W / 16W = L 574
 18W / 32W = L 1134
 27W / 36W = L 1694
 47W / 62W = L 2255

11W
 1300 lm
 3000K **AG0E1XK9L10BPLX**
 4000K **AG0E1XK9L10APLX**

16W
 2200 lm
 3000K **AG0E1XK9L20BPLX**
 4000K **AG0E1XK9L20APLX**

18W
 2600 lm
 3000K **AG0E1XK9L26BPLX**
 4000K **AG0E1XK9L26APLX**

32W
 4400 lm
 3000K **AG0E1XK9L44BPLX**
 4000K **AG0E1XK9L40APLX**

27W
 3900 lm
 3000K **AG0E1XK9L39BPLX**
 4000K **AG0E1XK9LA30APLX**

36W
 5200 lm
 3000K **AG0E1XK9L88BPLX**
 4000K **AG0E1XK9L88APLX**

47W
 6600 lm
 3000K **AG0E1XK9L66BPLX**
 4000K **AG0E1XK9L66APLX**

62W
 8800 lm
 3000K **AG0E1XK9LA40BPLX**
 4000K **AG0E1XK9LA40APLX**